

From: **Mtmkirk@aol.com**  
Subject: **602 CRATE RULES**  
Date: **January 26, 2015, 5:00 PM**  
To: **mrk1147@yahoo.com**

## **SANTA MARIA RACEWAY**

### **602 CRATE RULES**

**GM602 ENGINE OPTION AND SPECIFICATIONS:** All cars utilizing a GM602 crate engine must clearly display on both front roof posts the word CRATE. Must be contrasting in color from body, minimum two inches tall. Markers not acceptable.

**(A) CRATE ENGINE:** Must use unaltered sealed GM #88958602 or #19258602 crate engine. Upon inspection, any different, altered or missing GM seal bolts will result in disqualification, loss of all SMR points for the season, \$1,000 fine and a 30-day suspension from all SMR events. \$250 fine for any crate engine not using OEM pushrods, valve springs or rocker arms.

**(B) CARBURETOR:** 1 - two or four barrel carburetor. Two barrel must be gauge legal untouched 500 cfm Holley, model 4412. Four barrel may be any untouched gauge legal four barrel up to 650 cfm. 650 cfm carburetors may not exceed 1 1/4" venturi and 1-11/16" throttle bore.

"Down leg" style discharge only. No anular discharge.

Maximum 1" carb spacer.

*THE RACE DIRECTOR MAY MODIFY THE WEIGHT RULE FOR THESE CARS IN ORDER TO MAKE SURE THEY ARE COMPETITIVE OR ADD RESTRICTED PLATE*